

WHAT IS CLAIMED IS:

1. An automated method of provisioning a virtual private network, the method comprising:

receiving a high level description of a topology of a network;
applying a set of rules to the topology of the network to produce a plurality of route targets associated with virtual private networks to be assigned to the network;
grouping a set of route targets from the plurality of route targets with respect to each customer equipment node within the network to form a group of route target sets;
removing duplicate sets of route targets from the group of route target sets to form a reduced size set of route targets;
assigning each set of route targets in the reduced size set of route targets to a virtual routing and forwarding VRF element and all the CEs with the same RT set on one PE share one VRF; and
generating an output file including output data that identifies each of the VRFs and the associated route targets assigned to each of the VRFs.

2. The method of claim 1, further comprising communicating the output data to a network element within the network.

3. The method of claim 1, further comprising communicating the output file to a system having a display.

4. The method of claim 4, further comprising displaying a report based on the output data.

5. The method of claim 1, wherein the high level description of the topology of the network comprises a plurality of data entries, a first set of the data entries identifying customer edge (CE) routers, a second set of data entries identifying provider edge routers corresponding to each of the customer edge routers, a third set of the data entries identifying a topology type for each of the virtual private networks.

6. The method of claim 5, wherein the network element is a VRF component within a data router and wherein the topology type is selected from full mesh, central service and hub and spoke topology types.

7. The method of claim 5, wherein the network is a multi protocol label switching (MPLS) network and wherein the plurality of data entries has a table format wherein the rows are virtual private networks, a set of columns are defined by the customer edge routers and the table entries include the associated provider edge routes.

8. A computer network operations system comprising:
a terminal having a display portion;
a data input device to receive input from a user;
a computer system having a memory and a processor, the computer system coupled to the terminal and to the data input device;
wherein the display portion of the terminal provides an input screen having a data format configured to prompt the user to provide high-level network topology data via the data input device, the high-level network topology data including virtual private network information with respect to a backbone data network;
wherein the computer system converts the high-level network topology data into a set of route targets to be assigned to virtual routing and forwarding elements, the set of route targets stored in the memory.

9. The computer network operations system of claim 8, wherein the backbone data network comprises a multi protocol label switching (MPLS) network.

10. A method of provisioning a virtual private network service, the method comprising:
- providing a set of rules regarding assignment of route targets for each of a plurality of virtual private networks;
 - configuring provider edge routers of a backbone network;
 - configuring customer edge routers, each of the customer edge routers having a relationship link to at least one of the provider edge routers;
 - assigning route targets to each of the customer edge routers based on topology requirements of the backbone network and based on the set of rules; and
 - configuring each of the VRFs and RTs on the corresponding provider edge routers to form a logical topology.
11. The method of claim 10, further comprising adding an additional CE to one of the plurality of virtual private networks to form a modified logical topology.
12. The method of claim 10, further comprising deleting one of the CEs of one of the plurality of virtual private networks to form a modified logical topology.
13. The method of claim 11, wherein the modified logical topology has a new VPN with respect to the logical topology.
14. The method of claim 12, wherein the modified logical topology has a removed VPN with respect to the logical topology.
15. The method of claim 10, further comprising communicating the logical topology to a remote computer system wherein the logical topology includes a modified topology type, the modified topology type changed from Hub and Spoke to a full mesh arrangement.
16. The method of claim 15, further comprising displaying a graphical representation of the logical topology to a user of a terminal coupled to the computer system.

17. The method of claim 16, wherein the terminal is an operations terminal of a network management system, the network management system tied to the backbone network.

18. The method of claim 10, wherein the high level description of the topology of the network comprises a plurality of data entries, a first set of the data entries identifying CEs, a second set of data entries identifying PEs corresponding to each of the CEs, a third set of the data entries identifying a topology type for each of the virtual private networks.

19. The method of claim 10, wherein the network element is a VRF component within a data router and wherein the topology type is selected from full mesh, central service and hub and spoke topology types.

20. The method of claim 10, wherein the network is a MPLS network and wherein the plurality of data entries has a table format wherein the rows are virtual private networks, a column includes the network topology type, a set of columns are defined by the CEs and the table entries include the associated PEs.

21. A system to monitor a backbone network, the system comprising:
a terminal having a display portion;
a data input device to receive input from a user;
a computer system having a memory and a processor, the computer system
coupled to the terminal and to the data input device;
wherein the display portion of the terminal provides an input screen having a data
format configured to prompt the user to provide high-level network
topology data via the data input device, the backbone network including a
plurality of CEs, a plurality of PEs, a plurality of virtual routing and
forwarding components, a plurality of route targets, and a plurality of
virtual private networks and wherein the high level network topology data
identifies the CEs, the PEs within each of the virtual private networks; and
wherein the computer system includes a set of rules to convert the high-level
network topology data into a set of route targets to be assigned to virtual
routing and forwarding (VRF) elements, the set of route targets stored in
the memory.

22. The system of claim 21, wherein the set of rules includes a first set of rules to
handle route target to VRF mapping based on a meshed topology and a second set of
rules to handle route targets to VRF mapping for a hub and spoke topology and a third set
of rules to handle route targets to VRF mapping for a central service topology.

23. The system of claim 22, wherein the second set of rules includes an import
rule and an export rule.

24. The system of claim 23, wherein the second set of rules applies to two route
targets for a particular VRF component.

25. The system of claim 21, wherein the memory further stores a software
program to generate and deploy the set of route targets into a physical network router
node.

26. The system of claim 21, wherein the memory further includes a VRF to route target data mapping for each of a plurality of PEs and wherein all the CEs with the same RT set on one PE share one VRF.